

## SMALL T5 OR LED EMERGENCY FLUORESCENT BULKHEAD LUMINAIRES



### SPECIFICATION

- Off-white polycarbonate body
- Clear linear prismatic or opal polycarbonate covers
- LED version
- Emergency, AutoTest and Scanlight AT versions
- Three hour, maintained or non-maintained operation
- Optional self-adhesive legend kit
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas
- Fitted with 3500K lamp or 4000K LEDs

Luminaires used at Scanlight AT platforms 1 and 2 may self-test at any time. Consequently, caution should be exercised in situations where this may be inconvenient (such as hotel rooms or hospital wards). Scanlight AT platform 3 has inhibit features.




### LED CHARACTERISTICS

Ra	°K	L70/B10	LL/CW 70.0
80+	4000	60K	
P/U	%	R/Rx	PF
P	>60	R	0.6

For LED characteristics explanation see [www.thorlux.com/led-characteristics](http://www.thorlux.com/led-characteristics)

### DIMENSIONS



### RANGE

LAMP	OPAL VERSION	CLEAR VERSION	APPROX. kg	TYPE
<b>Emergency</b>				
4W LED	<b>EFB 15466</b>	<b>EFB 15477 ▲</b>	3.3	Maintained
4W LED	<b>EFB 15467</b>	<b>EFB 15478 ▲</b>	3.0	Non-maintained
1 x 8W T5	<b>EFB 13250E</b>	<b>EFB 10010E</b>	2.8	Maintained
1 x 8W T5	<b>EFB 13251</b>	<b>EFB 10009</b>	2.6	Non-maintained
<b>AutoTest</b>				
4W LED +	<b>TFB 15466</b>	<b>TFB 15477 ▲</b>	3.3	Maintained
4W LED +	<b>TFB 15467</b>	<b>TFB 15478 ▲</b>	3.0	Non-maintained
1 x 8W T5	<b>TFB 13250E</b>	<b>TFB 10010E</b>	2.8	Maintained
1 x 8W T5	<b>TFB 13251</b>	<b>TFB 10009</b>	2.6	Non-maintained
<b>Scanlight AT</b>				
1 x 8W T5	<b>DFB 13251</b>	<b>DFB 10009</b>	2.6	Non-maintained

+ Can be connected to Scanlight AT using DALI connections

▲ Not suitable for use with Legend Kits. Opal versions recommended

### LEGEND KITS

ISO 7010 self adhesive legend kit (inc. A, B, C and D) - Cat. No. EFB 15258\*



EURO self adhesive legend kit (inc. E, F and G) - Cat. No. EFB 9137\*



\* Order separately from luminaire