

SMALL T5 OR LED EMERGENCY FLUORESCENT BULKHEAD LUMINAIRES



SPECIFICATION

- Off-white polycarbonate body
- Clear linear prismatic or opal polycarbonate covers
- LED version
- Emergency, AutoTest and Scanlight AT versions
- Three hour, maintained or non-maintained operation
- Optional self-adhesive legend kit
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas
- Fitted with 3500K lamp or 4000K LEDs

Luminaires used at Scanlight AT platforms 1 and 2 may self-test at any time. Consequently, caution should be exercised in situations where this may be inconvenient (such as hotel rooms or hospital wards). Scanlight AT platform 3 has inhibit features.




LED CHARACTERISTICS

Ra	°K	L70/B10	LL/CW 70.0
80+	4000	60K	
P/U	%	R/Rx	PF
P	>60	R	0.6

For LED characteristics explanation see www.thorlux.com/led-characteristics

DIMENSIONS



RANGE

LAMP	OPAL VERSION	CLEAR VERSION	APPROX. kg	TYPE
Emergency				
4W LED	EFB 15466	EFB 15477 ▲	3.3	Maintained
4W LED	EFB 15467	EFB 15478 ▲	3.0	Non-maintained
1 x 8W T5	EFB 13250E	EFB 10010E	2.8	Maintained
1 x 8W T5	EFB 13251	EFB 10009	2.6	Non-maintained
AutoTest				
4W LED +	TFB 15466	TFB 15477 ▲	3.3	Maintained
4W LED +	TFB 15467	TFB 15478 ▲	3.0	Non-maintained
1 x 8W T5	TFB 13250E	TFB 10010E	2.8	Maintained
1 x 8W T5	TFB 13251	TFB 10009	2.6	Non-maintained
Scanlight AT				
1 x 8W T5	DFB 13251	DFB 10009	2.6	Non-maintained

+ Can be connected to Scanlight AT using DALI connections

▲ Not suitable for use with Legend Kits. Opal versions recommended

LEGEND KITS

ISO 7010 self adhesive legend kit (inc. A, B, C and D) - Cat. No. EFB 15258*



EURO self adhesive legend kit (inc. E, F and G) - Cat. No. EFB 9137*



* Order separately from luminaire