



Body detail



Emergency LED array



LED EMERGENCY LUMINAIRES FOR HIGH RISK AREAS

IP20 IP44 BELOW CEILING (IP44 versions only) CE LED


SPECIFICATION

- High pressure die-cast bezel finished full polyester, non-yellowing white
- Injection moulded polycarbonate body housing
- Supplied with remote gear unit fitted with 2m lead
- Aids compliance with BS5266-1:2011 for areas where enhanced illuminance is needed at specific locations
- Ideally suited for use in suspended ceilings only - serviceable batteries located within gear unit placed in ceiling void


RANGE

LED	OPEN	IP44 - CLEAR GLASS PANEL	DURATION	APPROX. kg	TYPE
Emergency 5W	ELO 16386	ELO 16761	3-Hour	1.8	Non-maintained
AutoTest 5W	TLO 16386	TLO 16761	3-Hour	1.8	Non-maintained
Scanlight AT 5W	DLO 16386	DLO 16761	3-Hour	1.8	Non-maintained

PHOTOMETRIC GUIDE





OPEN
Luminaire Lumen Output
5W = 495lm



IP44 - CLEAR GLASS PANEL
Luminaire Lumen Output
5W = 435lm

DIMENSIONS



All dimensions in millimetres