



## RECESSED LUMINAIRES FOR CORRIDOR APPLICATIONS



### SPECIFICATION

- Steel body, welded and finished steel frame, finished full polyester non-yellowing satin white (RAL 9016)
- Ultra low glare V-blade louvre or general low glare faceted cross-blade louvre set behind a clear polycarbonate cover
- Prismatic polycarbonate cover version (T5)
- Satin polycarbonate cover version (LED)
- Snap fix screw-less frame
- Supplied with side arm suspension kit
- Fits 24mm exposed T-bar ceilings (other ceiling type options available to special order)
- Fitted with 4000K lamp or LEDs

### LED CHARACTERISTICS

Ra 80+	°K 4000	L70/B10 50K	LL/CW <b>79.1</b>
P/U P	% >85	R/Rx R	

For LED characteristics explanation see [www.thorlux.com/led-characteristics](http://www.thorlux.com/led-characteristics)

## RANGE

NOMINAL SIZE (mm)	LAMP	CAT. No.	APPROX. kg	CIRCUIT
<b>V-blade louvre versions</b>				
1200 x 150	46W LED 1 x 54W T5	<b>GP 16249</b>	6.7	L/A
		<b>GP 16250</b>	6.0	J/T
<b>Faceted cross-blade louvre versions</b>				
1200 x 150	46W LED 1 x 54W T5	<b>GP 16251</b>	6.7	L/A
		<b>GP 16252</b>	6.0	J/T
<b>Satin polycarbonate versions</b>				
1200 x 150	46W LED	<b>GP 16253</b>	5.7	L/A
<b>Prismatic polycarbonate versions</b>				
1200 x 150	1 x 54W T5	<b>GP 16254</b>	5.0	J/T

**CIRCUIT TYPE** - suffix catalogue number with:

**J** - non-dimming (HF fluorescent) / **L** - non-dimming (LED) / **T** - dimming (DSI) / **A** - dimming (DALI) e.g. **GP 16249L** etc.

**EMERGENCY VERSION** - prefix catalogue number with:

**EGP** - Emergency / **TGP** - AutoTest / **DGP** - Scanlight AT e.g. **EGP 16249L** etc.

Emergency, AutoTest and Scanlight AT versions add 0.7kg to weights listed or 0.3kg for LED versions

## DIMENSIONS

