






RANGE

NOMINAL SIZE (mm		LUMINAIRE ONLY	LENGTH (mm)	APPROX. kg	LUMINAIRE COMPLETE WITH BACK TRUNKING	APPROX. kg
1000	2 x 29W LED uplighter and DALI dimming downlighter	SMD 16376	1017	4.2	SMD 16380	7.5
	2 x 39W T5 non-dimming uplighter and DSI dimming downlighter	SMD 16176	1017	4.2	SMD 16177	7.5
1300	2 x 38W LED uplighter and DALI dimming downlighter	SMD 16378	1317	6.2	SMD 16382	10.2
	2 x 54W T5 non-dimming uplighter and DSI dimming downlighter	SMD 14860	1317	6.2	SMD 14862	10.2

INTEGRAL NIGHT LIGHT VERSION - suffix catalogue number with: N e.g. SMD 16376N etc.

DIMENSIONS



BEDHEAD LUMINAIRES



SPECIFICATION

- Shallow depth extruded aluminium body with die-cast aluminium ends designed for easy cleaning
- Finished full polyester non-yellowing satin white (RAL 9016)
- Complies with the CIBSE 2008 Hospital Lighting Guide (LG2)
- Separate switching facility for up and down light operation
- Dimmable downlight for patient comfort
- Optional centrally mounted 1W LED night light contained within the lower (downlight) compartment
- Curved and sloping top discourages use as a shelf and helps minimise dust build -up
- Version with back trunking section
- Complies with BS EN 60598-2-25
- Supplied with 4000K lamps or LEDs

LED CHARACTERISTICS Ra °K L70/B10 LL/CW 80+ 4000 50K LL/CW P/U % R/Rx PF 77.6

>0.90

For LED characteristics explanation see <u>www.thorlux.com/led-characteristics</u>

R

Ρ

>85



