


MINA-L




DIMENSIONS



Cut-out - 156mm dia.
Minimum ceiling void - 186mm

Standard Remote Driver





ADJUSTABLE RECESSED ACCENT DOWNLIGHTS



SPECIFICATION

- Die-cast aluminium ring assembly finished satin white
- Black and Silver finishes available to special order*
- 17°, 28° and 41° beam angle versions
- 355° azimuth adjustment
- 60° vertical adjustment
- Injection moulded, black, anti-glare reflector bezel
- Supplied with remote gear unit(s) fitted with 2m lead
- Luminaires can be supplied pre-wired with a purpose made 1m connection lead for plugging directly into the Smart Hub
- Fitted with CRI 90 LEDs with enhanced R9 value. Suitable for retail applications
- CRI 80 available*
- 3000K and 4000K versions

* Minimum order quantity applies

RANGE

LED	17° BEAM	28° BEAM	41° BEAM	APPROX. kg	CIRCUIT
20W - 3000K	MA17970	MA17978	MA17986	1.3	L/A
28W - 3000K	MA17971	MA17979	MA17987	1.3	L/A
35W - 3000K	MA17972	MA17980	MA17988	1.3	L/A
20W - 4000K	MA17974	MA17982	MA17990	1.3	L/A
28W - 4000K	MA17975	MA17983	MA17991	1.3	L/A
35W - 4000K	MA17976	MA17984	MA17992	1.3	L/A

CIRCUIT TYPE - suffix catalogue number with:

L - non-dimming (LED) / **A** - dimming (DALI) e.g. **MA 17970L** etc.

HUB VERSIONS - suffix catalogue number with **SHL** e.g. **MA 17970LSHL**