

PITCH-L





TRACK MOUNTED ADJUSTABLE SPOTLIGHTS



SPECIFICATION

- Extruded aluminium gear enclosure finished full polyester satin white
- High pressure die-cast aluminium spotlight body finished full polyester satin white
- Black and Silver finishes available to special order*
- 17°, 28° and 41° beam angle versions
- 355° azimuth adjustment
- 180° vertical adjustment
- Injection moulded, black, anti-glare reflector bezel
- Designed for installation into 3 Circuit or 3 Circuit and DALI track
- Fitted with CRI 90 LEDs with enhanced R9 value. Suitable for retail applications
- CRI 80 available*
- 3000K and 4000K versions

* Minimum order quantity applies

RANGE

| LED | 17° BEAM | 28° BEAM | 41° BEAM | APPROX. kg | CIRCUIT |
|-------------|------------------|------------------|------------------|------------|---------|
| 14W - 3000K | PTC 18120 | PTC 18128 | PTC 18136 | 1.6 | L/A |
| 20W - 3000K | PTC 18121 | PTC 18129 | PTC 18137 | 1.6 | L/A |
| 28W - 3000K | PTC 18122 | PTC 18130 | PTC 18138 | 1.6 | L/A |
| 35W - 3000K | PTC 18123 | PTC 18131 | PTC 18139 | 1.6 | L/A |
| 14W - 4000K | PTC 18124 | PTC 18132 | PTC 18140 | 1.6 | L/A |
| 20W - 4000K | PTC 18125 | PTC 18133 | PTC 18141 | 1.6 | L/A |
| 28W - 4000K | PTC 18126 | PTC 18134 | PTC 18142 | 1.6 | L/A |
| 35W - 4000K | PTC 18127 | PTC 18135 | PTC 18143 | 1.6 | L/A |

CIRCUIT TYPE - suffix catalogue number with:

L - non-dimming (LED) / A - dimming (DALI) e.g. **PTC 18120L** etc.

DIMENSIONS

