





TRACK MOUNTED ADJUSTABLE SPOTLIGHTS



SPECIFICATION

- Extruded aluminium gear enclosure finished full polyester satin white
- High pressure die-cast aluminium spotlight body finished full polyester satin white
- Black and Silver finishes available to special order*
- 19°, 30° and 38° beam angle versions
- 355° azimuth adjustment
- 180° vertical adjustment
- Injection moulded, black, anti-glare reflector bezel
- Designed for installation into 3 Circuit or 3 Circuit and DALI track
- Fitted with CRI 90 LEDs with enhanced R9 value. Suitable for retail applications
- CRI 80 available*
- 3000K and 4000K versions

* Minimum order quantity applies

RANGE

LED	19° BEAM	30° BEAM	38° BEAM	APPROX. kg	CIRCUIT
6W - 3000K	PTC 18100	PTC 18106	PTC 18112	1.2	L/A
14W - 3000K	PTC 18101	PTC 18107	PTC 18113	1.2	L/A
20W - 3000K	PTC 18102	PTC 18108	PTC 18114	1.2	L/A
6W - 4000K	PTC 18103	PTC 18109	PTC 18115	1.2	L/A
14W - 4000K	PTC 18104	PTC 18110	PTC 18116	1.2	L/A
20W - 4000K	PTC 18105	PTC 18111	PTC 18117	1.2	L/A

CIRCUIT TYPE - suffix catalogue number with:

L - non-dimming (LED) / **A** - dimming (DALI) e.g. **PTC 18100L** etc.

DIMENSIONS

