





With Barn Doors



Without Barn Doors

TRACK MOUNTED ADJUSTABLE SPOTLIGHT



SPECIFICATION

- High pressure die-cast aluminium gear enclosure finished full polyester satin white
- High pressure die-cast aluminium spotlight body finished full polyester satin white
- Black and Silver finishes available to special order*
- 17°, 26° and 47° beam angle
- 355° azimuth adjustment
- 90° vertical adjustment
- Injection moulded, black, anti-glare reflector bezel
- Barn door option to control light distribution
- Designed for installation into 3 Circuit or 3 Circuit and DALI track
- Fitted with CRI 90 LEDs with enhanced R9 value. Suitable for retail applications
- CRI 80 available*
- 3000K and 4000K versions

* Minimum order quantity applies

RANGE

LED	17° BEAM	26° BEAM	47° BEAM	APPROX. kg	CIRCUIT
Without Barn Door					
14W - 3000K	PIV 18150	PIV 18156	PIV 18162	1.7	L/A
20W - 3000K	PIV 18151	PIV 18157	PIV 18163	1.7	L/A
28W - 3000K	PIV 18152	PIV 18158	PIV 18164	1.7	L/A
14W - 4000K	PIV 18153	PIV 18159	PIV 18165	1.7	L/A
20W - 4000K	PIV 18154	PIV 18160	PIV 18166	1.7	L/A
28W - 4000K	PIV 18155	PIV 18161	PIV 18167	1.7	L/A
With Barn Door					
14W - 3000K	PIV 18170	PIV 18176	PIV 18182	1.8	L/A
20W - 3000K	PIV 18171	PIV 18177	PIV 18183	1.8	L/A
28W - 3000K	PIV 18172	PIV 18178	PIV 18184	1.8	L/A
14W - 4000K	PIV 18173	PIV 18179	PIV 18185	1.8	L/A
20W - 4000K	PIV 18174	PIV 18180	PIV 18186	1.8	L/A
28W - 4000K	PIV 18175	PIV 18181	PIV 18187	1.8	L/A

CIRCUIT TYPE - suffix catalogue number with:
L - non-dimming (LED) / **A** - dimming (DALI) e.g. **PIV 18150L** etc.

DIMENSIONS

