





CIRCULAR RECESSED DOWNLIGHTS

IP65 BELOW CEILING    IP20 BELOW CEILING    IP20 ABOVE CEILING



SPECIFICATION

- High pressure die-cast aluminium bezel finished full polyester satin white
- Injection moulded, black, anti-glare reflector bezel
- 30° and 38° beam angle versions
- IP65 versions with frosted glass
- Sprung suspension arms for rapid installation
- Supplied with remote gear unit fitted with 2m lead
- Luminaires can be supplied pre-wired with a purpose made 1m connection lead for plugging directly into the Smart Hub
- Fitted with CRI 90 LEDs with enhanced R9 value. Suitable for retail applications
- CRI 80 available\*
- 3000K and 4000K versions

\* Minimum order quantity applies

RANGE

LED	IP20 30° BEAM	IP20 38° BEAM.	APPROX. kg	IP65 FROSTED GLASS.	APPROX. kg	CIRCUIT
14W - 3000K	<b>TEG 18032</b>	<b>TEG 18036</b>	1.0	<b>TEG 18044</b>	0.9	L/A
20W - 3000K	<b>TEG 18033</b>	<b>TEG 18037</b>	1.0	<b>TEG 18045</b>	0.9	L/A
14W - 4000K	<b>TEG 18034</b>	<b>TEG 18038</b>	1.0	<b>TEG 18046</b>	0.9	L/A
20W - 4000K	<b>TEG 18035</b>	<b>TEG 18039</b>	1.0	<b>TEG 18047</b>	0.9	L/A

CIRCUIT TYPE - suffix catalogue number with:  
**L** - non-dimming (LED) / **A** - dimming (DALI) e.g. **TEG 18032L** etc.

HUB VERSIONS - suffix catalogue number with **SHL** e.g. **TEG 18032SHL**

DIMENSIONS

