



LED TAMPER-RESISTANT AND IMPACT RESISTANT SURFACE LUMINAIRES

IP65 IK10++ CE LED

SPECIFICATION

- Robust and durable extruded aluminium body finished white (RAL 9010)
- Die cast aluminium end caps finished white (RAL 9010)
- Clear prismatic polycarbonate lens
- Body dissipates heat, ensuring long control gear life in higher ambient temperatures
- Suitable for both individual and in-line mounting
- Fitted with 4000K LEDs

LED CHARACTERISTICS

Ra	°K	L70/B10	LL/CW
80	4000	50K	
P/U	%	R/Rx	83.0
P	>85	R	
		PF	
		0.95	

For LED characteristics explanation see www.thorlux.com/led-characteristics

RANGE

LENGTH (mm)	LED	CAT. No.	APPROX. kg	CIRCUIT
697	19W	VT 17215	5.0	L/A
1307	56W	VT 17216	9.0	L/A

CIRCUIT TYPE - suffix catalogue number with:
L - non-dimming (LED) / **A** - dimming (DALI) e.g. **VT 17215L** etc.


EMERGENCY VERSION (56W version only) - prefix catalogue number with:
EVT - Emergency e.g. **EVT 17216L** etc.
 Emergency versions add 0.3kg to weights listed.

DIMENSIONS



All dimensions in millimetres

PHOTOMETRIC GUIDE



Luminaire Lumen Output
 19W = 1635lm
 56W = 5060lm