

ZENITH-M





## CEILING MOUNTED ADJUSTABLE SPOTLIGHTS



### SPECIFICATION

- Extruded aluminium gear enclosure finished full polyester satin white
- High pressure die-cast aluminium spotlight body finished full polyester satin white
- Black and Silver finishes available to special order\*
- Integral electronic control gear
- 30° and 38° beam angle versions
- 355° azimuth adjustment
- 180° vertical adjustment
- Injection moulded, black, anti-glare reflector bezel
- Fitted with 0.5m lead
- Luminaires can be supplied pre-wired with a purpose made 1m connection lead for plugging directly into the Smart Hub
- Suitable for ceiling mount only
- Fitted with CRI 90 LEDs with enhanced R9 value. Suitable for retail applications
- CRI 80 available\*
- 3000K and 4000K versions

\* Minimum order quantity applies

### RANGE

LED	30° BEAM	38° BEAM	APPROX. kg	CIRCUIT
14W - 3000K	<b>ZEN 18070</b>	<b>ZEN 18074</b>	1.2	L/A
20W - 3000K	<b>ZEN 18071</b>	<b>ZEN 18075</b>	1.2	L/A
14W - 4000K	<b>ZEN 18072</b>	<b>ZEN 18076</b>	1.2	L/A
20W - 4000K	<b>ZEN 18073</b>	<b>ZEN 18077</b>	1.2	L/A

CIRCUIT TYPE - suffix catalogue number with:

**L** - non-dimming (LED) / **A** - dimming (DALI) e.g. **ZEN 18070L** etc.

**HUB VERSIONS** - suffix catalogue number with **SHL** e.g. **ZEN 18070LSHL**

### DIMENSIONS

