

JUNO B



RANGE


LED	CAT. No.	APPROX. kg
30W	JUN 17674L	7.6
60W	JUN 17675L	7.6

CIRCUIT TYPE - L - non-dimming (LED)


OPTIONS

DESCRIPTION	SUFFIX	EXAMPLE
Photocell	PC	JUN 17674LPC

DIMENSIONS



PHOTOMETRIC GUIDE



Luminaire Lumen Output:
30W = 3975lm
60W = 7340lm

LED POLE TOP AMENITY LUMINAIRES

IP66 IK10 CE LED WINDAGE - 0.04m²

SPECIFICATION

- Strong high pressure die-cast aluminium top and column mount finished full polyester powder coat silver (RAL9006)
- High-impact UV stabilised polycarbonate cover rated IK10
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Fitted with 6m flying lead
- Photocell option
- Zero upward light
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	70+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	100K - L90/B10
PROTECTION	-
DRIVER EFFICIENCY	>88%
REPLACEABLE	YES
POWER FACTOR	>0.95
LL/CW	116.9

For LED characteristics explanation see
www.thorlux.com/led-characteristics