



LED AREA FLOODLIGHTS



WINDAGE - 0.06m²

SPECIFICATION

- Strong high pressure die-cast aluminium top and column mount finished full polyester powder coat silver (RAL9006)
- High-impact UV stabilised polycarbonate cover rated IK10
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Fitted with 6m flying lead
- Smart External versions with intelligent lighting control for use up to 6 metres mounting height
- Optional SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit.
- Photocell option
- Zero upward light
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	70+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	100K - L90/B10
PROTECTION	-
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.95

LL/CW 104.3

For LED characteristics explanation see www.thorlux.com/led-characteristics



Learn more about SmartScan at:
www.thorlux.com/smartsan

RANGE

	LED	CAT. No.	APPROX. kg	CIRCUIT
SMART EXTERNAL	52W	JUN 17676	8.9	D/SS
	78W	JUN 17677	8.9	D/SS
STANDARD	52W	JUN 17678L	8.8	
	78W	JUN 17679L	8.8	

CIRCUIT TYPE - suffix catalogue number with:


SMART D - Smart External / SS - SmartScan

STANDARD L - non-dimming (LED) e.g. JUN 17676SS etc.

OPTIONS

DESCRIPTION	SUFFIX	EXAMPLE
Photocell (standard versions only)	PC	JUN 17678LPC

PHOTOMETRIC GUIDE



Luminaire Lumen Output:
52W = 6360lm
78W = 9155lm

DIMENSIONS

