

CLARA 90





## WALL MOUNTED LED UPLIGHTERS



### SPECIFICATION

- White injection moulded polycarbonate body (RAL 9016)
- Silver option (RAL 9006)
- High efficiency optical system with clear polycarbonate cover
- 60,000 hour life expectancy
- LED failure protection
- Fitted with 4000K LEDs

### LED CHARACTERISTICS

CRI	<b>80+</b>
COLOUR TEMPERATURE	<b>4000K</b>
RATED LIFE (HOURS)	<b>100K - L90/B10</b>
PROTECTION	<b>LED PROTECT</b>
DRIVER EFFICIENCY	<b>&gt;80%</b>
REPLACEABLE	<b>YES</b>
POWER FACTOR	<b>&gt;0.95</b>

**LL/CW 62.9**

For LED characteristics explanation see [www.thorlux.com/led-characteristics](http://www.thorlux.com/led-characteristics)


### RANGE

LED	CAT. No.	APPROX. kg	CIRCUIT
10W	<b>CA 15851</b>	1.0	L/A
20W	<b>CA 15852</b>	1.0	L/A

**CIRCUIT TYPE** - suffix catalogue number with:  
**L** - non-dimming (LED) / **A** - dimming (DALI) e.g. **CA 15851L** etc.

**FINISH OPTION** - suffix catalogue number with:  
**SV3** - Silver e.g. **CA 15851LSV3** etc.

### PHOTOMETRIC GUIDE



#### LED

Luminaire Lumen Output  
 10W = 755lm  
 20W = 1315lm

### DIMENSIONS

