





LEDs covered by satin tube to reduce glare and diffuse light



Aluminium reflector version



Polycarbonate refractor version

## INTEGRAL LED PENDANTS



### SPECIFICATION

- Refractor in polycarbonate and reflector in anodised aluminium
- Gloss silver finish extruded aluminium body
- Satin tube over LEDs reduces glare and diffuses light
- Fitted with 2m black cable
- Fitted with 4000K LEDs

### LED CHARACTERISTICS

CRI	<b>80+</b>
COLOUR TEMPERATURE	<b>4000K</b>
RATED LIFE (HOURS)	<b>77K - L80/B10</b>
PROTECTION	<b>LED PROTECT</b>
DRIVER EFFICIENCY	<b>&gt;85%</b>
REPLACEABLE	<b>YES</b>
POWER FACTOR	<b>&gt;0.9</b>

**LL/CW 84.1**

For LED characteristics explanation see [www.thorlux.com/led-characteristics](http://www.thorlux.com/led-characteristics)

## RANGE

LED	CAT. No.	HEIGHT (mm)	DIAMETER (mm)	APPROX. kg
<b>Polycarbonate Refractor</b>				
24W	<b>SH 15156L</b>	365	312	2.0
36W	<b>SH 15157L</b>	365	312	2.0
<b>Aluminium Reflector</b>				
24W	<b>SH 15158L</b>	365	312	2.0
36W	<b>SH 15159L</b>	365	312	2.0

CIRCUIT TYPE - L - non-dimming (LED)