



## HIGH PERFORMANCE LED POLE TOP LUMINAIRES



WINDAGE - 0.04m<sup>2</sup>

### SPECIFICATION

- Strong high pressure die-cast aluminium top and column mount finished full polyester (RAL9006)
- High impact UV stabilised polycarbonate cover rated IK10
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Fitted with 10m flying lead
- Photocell option
- Zero upward light
- Fitted with 4000K LEDs

### RANGE

| LED* | SYMMETRIC DISTRIBUTION | ASYMMETRIC DISTRIBUTION | APPROX. kg |
|------|------------------------|-------------------------|------------|
| 37W  | <b>JUN 19200</b>       | <b>JUN 19202</b>        | 7.6        |
| 78W  | <b>JUN 19201</b>       | <b>JUN 19203</b>        | 7.6        |

CIRCUIT TYPE - L - non-dimming (LED)


### OPTIONS

| DESCRIPTION | SUFFIX    | EXAMPLE             |
|-------------|-----------|---------------------|
| Photocell   | <b>PC</b> | <b>JUN 190200PC</b> |

### ACCESSORIES


| DESCRIPTION                   | CAT. No.         |
|-------------------------------|------------------|
| Backlight reducing shield kit | <b>JUN 19204</b> |

### PHOTOMETRIC GUIDE



#### ASYMMETRIC DISTRIBUTION

Luminaire Lumen Output:  
37W = 5135lm  
78W = 9595lm



#### SYMMETRIC DISTRIBUTION

Luminaire Lumen Output:  
37W = 5155lm  
78W = 9630lm

### LED CHARACTERISTICS

|                    |                       |
|--------------------|-----------------------|
| CRI                | <b>70</b>             |
| COLOUR TEMPERATURE | <b>4000K</b>          |
| RATED LIFE (HOURS) | <b>100K - L80/B10</b> |
| PROTECTION         | <b>LUX GUARD</b>      |
| DRIVER EFFICIENCY  | <b>93%</b>            |
| REPLACEABLE        | <b>YES</b>            |
| POWER FACTOR       | <b>&gt;0.95</b>       |

**LL/CW 117.2**

For LED characteristics explanation see [www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

### DIMENSIONS

