



Smart External version



LED AREA FLOODLIGHTS

IP66 IK10 CE LED

WINDAGE - 0.06m²

SPECIFICATION

- Strong high pressure die-cast aluminium top and column mount finished full polyester powder coat silver (RAL9006)
- High-impact UV stabilised polycarbonate cover rated IK10
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Fitted with 6m flying lead
- Smart External versions with intelligent lighting control for use up to 6 metres mounting height
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit
- Photocell option
- Zero upward light
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	70+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	100K - L90/B10
PROTECTION	-
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.95

LL/CW **104.3**

For LED characteristics explanation see www.thorlux.com/led-guide

SmartScan Configurations



Find out more at www.thorlux.com/smartsan

RANGE

	LED	CAT. No.	APPROX. kg
SMART EXTERNAL	52W	JUN 17676SS	8.9
	78W	JUN 17677SS	8.9
STANDARD	52W	JUN 17678L	8.8
	78W	JUN 17679L	8.8


CIRCUIT TYPE -

SMART EXTERNAL	SS - SmartScan
STANDARD	L - non-dimming (LED)

OPTIONS

DESCRIPTION	SUFFIX	EXAMPLE
Photocell (<i>standard versions only</i>)	PC	JUN 17678LPC

PHOTOMETRIC GUIDE



Luminaire Lumen Output:
52W = 6360lm
78W = 9155lm

DIMENSIONS

