



Medica with back trunking section




Medica without back trunking section

RANGE

NOMINAL SIZE (mm)	LAMP	LUMINAIRE ONLY	LENGTH (mm)	APPROX. kg	LUMINAIRE COMPLETE WITH BACKTRUNKING	APPROX. kg
1000	2 x 29W LED uplighter and DALI dimming downlighter	SMD 16376	1017	4.2	SMD 16380	7.5
	2 x 39W T5 non-dimming uplighter and DSI dimming downlighter	SMD 16176	1017	4.2	SMD 16177	7.5
1300	2 x 38W LED uplighter and DALI dimming downlighter	SMD 16378	1317	6.2	SMD 16382	10.2
	2 x 54W T5 non-dimming uplighter and DSI dimming downlighter	SMD 14860	1317	6.2	SMD 14862	10.2

INTEGRAL NIGHT LIGHT VERSION - suffix catalogue number with: **N** e.g. **SMD 16376N** etc.

DIMENSIONS



BEDHEAD LUMINAIRES

IP40 CE T5 LED

SPECIFICATION

- Shallow depth extruded aluminium body with die-cast aluminium ends designed for easy cleaning
- Finished full polyester non-yellowing satin white (RAL 9016)
- Complies with the CIBSE 2008 Hospital Lighting Guide (LG2)
- Separate switching facility for up and down light operation
- Dimmable downlight for patient comfort
- Optional centrally mounted 1W LED night light contained within the lower (downlight) compartment
- Curved and sloping top discourages use as a shelf and helps minimise dust build-up
- Version with back trunking section
- Complies with BS EN 60598-2-25
- Supplied with 4000K lamps or LEDs

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	50K - L70/B10
PROTECTION	-
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.90
LL/CW	77.6

For LED characteristics explanation see www.thorlux.com/led-guide