



PHOTOMETRIC GUIDE




CLEAR COVER

Luminaire Lumen Output: 11W = 1665lm 16W = 2280lm



SATIN COVER


Luminaire Lumen Output: 11W = 1540lm 16W = 2145lm



LOW PROFILE SATIN COVER

Luminaire Lumen Output: 11W = 1605lm 16W = 2170lm

DIMENSIONS



Fixing points: 4 x Spot faces on 205mm centres (drill as required) and 1 central BESA box fixing

ACCESSORIES

DESCRIPTION	CAT. No.
Bezel for semi-recessed mounting (black finish)	PS 11876B
Bezel for semi-recessed mounting (white finish)	PS 11876W
Key for tamper-resistant screws	KEY 7979
Adaptor for cornice mounting (black finish)	PS 18886B
Adaptor for cornice mounting (white finish)	PS 18886W



Bezel for semi-recessed mounting - black



Cornice mounting

OPTIONS

DESCRIPTION	SUFFIX	EXAMPLE
Photocell ▲	PC	PS 14913PC
Microwave presence detector	MD	PS 14913MD

 ${\color{red}\blacktriangle}$ Not suitable for semi-recessed or cornice mounting



Clear cover





PRISMALETTE



Low profile satin cover version









SPECIFICATION

- Strong pressure die-cast LM2 aluminium body. Textured black, full polyester powder finish as standard
- White finish option
- Hinged clear prismatic or satin, fire-retardant polycarbonate cover
- Low profile satin polycarbonate cover version
- Tamper-resistant cover screws as standard
- Optional photocell control
- Bezel trim for semi-recessed mounting
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas
- Microwave presence detector option with stand-by light level feature
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	80	
COLOUR TEMPERATURE	4000K	
RATED LIFE (HOURS)	63K - L80/B10	
PROTECTION	LUX GUARD	
DRIVER EFFICIENCY	85%	
REPLACEABLE	YES	
POWER FACTOR	>0.95	
LL/CW	120.0	

For LED characteristics explanation see www.thorlux.com/led-guide

RANGE

	LAMP	CAT. No.	APPROX. kg
CLEAR COVER	11W LED	PS 17608L	2.8
	16W LED	PS 14913L	2.8
SATIN COVER	11W LED	PS 17609L	2.8
	16W LED	PS 14914L	2.8
LOW PROFILE	11W LED	PS 18420L	2.7
SATIN COVER	16W LED	PS 18421L	2.7
RETRO-FIT GEAR TRAY	11W LED	PS 14917L	0.8

WHITE OPTION - add suffix W - White e.g. PS 17608LW etc.

CIRCUIT TYPE - L - non-dimming (LED)

EMERGENCY VERSION - prefix catalogue number with: EPS - Emergency / TPS - AutoTest e.g. EPS 17608L etc. Emergency and AutoTest versions add 0.3kg