


# PROBE & PROBE-XL




## PHOTOMETRIC GUIDE



### PROBE - 24W LED

Initial lux levels at ground  
Luminaire Lumen Output:  
24W = 340lm



### PROBE-XL - 24W LED - 1040mm VERSION

Initial lux levels at ground  
Luminaire Lumen Output:  
24W = 1040lm

## ACCESSORIES

### DESCRIPTION

500mm root mounting extension  
Mounting adaptor for cast concrete

### CAT. No.

**PRB 12128**  
**PRB 12129**

# PROBE & PROBE-XL

Probe



Probe-XL



## IP66 BOLLARD LUMINAIRES



### SPECIFICATION

- Surface or root mounted accessories
- Integral control gear
- Fused mains terminal block
- Fitted with 4000K or 5700K LEDs

#### PROBE

- Low glare, round top bollard, aluminium construction finished black
- Clear polycarbonate cover

#### PROBE-XL

- High efficiency flat top bollard, aluminium construction finished black
- Linear prismatic polycarbonate cover

## RANGE

LED	PROBE VERSION	PROBE-XL 790mm VERSION	PROBE-XL 1040mm VERSION	APPROX. kg
24W - 4000K	PRB 17521L	PRB 17522L	PRB 17523L	9.8
24W - 5700K	PRB 14443L	PRB 14530L	PRB 14442L	9.8

CIRCUIT TYPE - L - non-dimming (LED)

## LED CHARACTERISTICS

CRI	70
COLOUR TEMPERATURE	4000K/5700K
RATED LIFE (HOURS)	100K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.95
<b>LL/CW</b>	<b>37.1</b>

For LED characteristics explanation see [www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

## DIMENSIONS

