

LED VANDAL-RESISTANT SEALED LUMINAIRES



SPECIFICATION

- 1.0mm steel body finished full polyester powder coated textured black
- 1.5mm steel front cover frame retained with tamper-resistant captive fixings (key supplied)
- SmartScan emergency version with wireless test status reporting
- Satin diffusing, 5mm thick polycarbonate front cover
- Continuous mounting available using infills
- Complies with M.O.D. JSP482 Document for 'Category C' areas
- High impact strength - IK10
- Fitted with 4000K LEDs

LED CHARACTERISTICS


CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	98K - L70/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.95

LL/CW 106.1

For LED characteristics explanation see www.thorlux.com/led-guide



PHOTOMETRIC GUIDE



Luminaire Lumen Output
34W = 4030lm
74W = 8745lm

RANGE

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg
1500	34W	VN 15758L	13.0
	74W	VN 15759L	13.2

CIRCUIT TYPE - L - non-dimming (LED)

EMERGENCY VERSION - prefix catalogue number with:
EVN - Emergency / **TVN** - AutoTest / **WVN** - SmartScan
e.g. **WVN 15758L** etc.
Add 0.7kg to weights listed.

ACCESSORIES

DESCRIPTION	CAT. No.	APPROX. kg
1500mm Infill (for use with continuous mounting)	VN 13327	13.6
Key for tamper-resistant screws	KEY 13328	-

DIMENSIONS



NOTE: Supply entries and fixing points to be drilled on site
IP65 integrity must be maintained

SmartScan Configurations



Find out more at www.thorlux.com/smartsan