



RECESSED COLOUR TEMPERATURE CHANGING LUMINAIRES WITH DOMED POLYCARBONATE DIFFUSER



SPECIFICATION

- Steel body finished full polyester, non-yellowing white
- Shallow body depth
- Domed diffuser provides wall and ceiling illumination
- Suitable for most ceiling types. Lay-in or pull-up with side arm suspensions (included with LED versions)
- Designed to exclude dust, dirt and flies. All control gear is outside the lamp enclosure and the diffuser frame is gasketted
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit (CA versions)
- Fitted with 3000K and 6500K LEDs for colour temperature control

WEB LINK >
 "PLUG AND PLAY"
 LIGHTING CABLE
 MANAGEMENT



LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K to 6500K
RATED LIFE (HOURS)	67K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9
LL/CW	105.6

For LED characteristics explanation see www.thorlux.com/led-characteristics

RANGE

COLOURACTIVE LUMINAIRE - with integral wireless SmartScan Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg
600 X 600	16W	SD 18807CA	6.9
	31W	SD 18808CA	6.9

COLOURCONTROL LUMINAIRE - for use with SmartScan Stand-alone Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg
600 X 600	16W	SD 17247CC	6.7
	31W	SD 17248CC	6.7

EMERGENCY VERSION - prefix catalogue number with:

ESD - Emergency / **TSD** - AutoTest / **WSD** - SmartScan (CA version only) e.g. **WSD18807CA** etc.
 Add 0.3kg to weights listed



DIMENSIONS

