



LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K to 6500K
RATED LIFE (HOURS)	63K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.95

LL/CW 102.4

For LED characteristics explanation see www.thorlux.com/led-characteristics

RANGE

COLOURACTIVE LUMINAIRE - with integral wireless SmartScan Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	LENGTH (mm)
1500	30W 37W	JUB 18801CA JUB 18802CA	6.6 6.6	1545

COLOURCONTROL LUMINAIRE - for use with SmartScan Stand-alone Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	LENGTH (mm)
1500	30W 37W	JUB 18804CC JUB 18805CC	6.5 6.5	1495

EMERGENCY VERSION - prefix catalogue number with:

EJB - Emergency / **TJB** - AutoTest / **WJB** - SmartScan (CA version only) e.g. **WJB18801CA** etc.
Add 0.3kg to weights listed

SURFACE MOUNTED COLOUR
TEMPERATURE CHANGING
SHALLOW PROFILE CONTROLLER
LUMINAIRES



SPECIFICATION

- Steel body finished full polyester, non-yellowing white
- Shallow profile with co-extruded 'Satin-Glo' polycarbonate controller
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit (CA versions)
- Fitted with 3000K and 6500K LEDs for colour temperature control

DIMENSIONS

