



# Kanby LED Controller

## COLOUR TEMPERATURE CHANGING LED CONTROLLER LUMINAIRES



### SPECIFICATION

- Steel body, gear cover and end caps finished full polyester, non-yellowing white
- Ultra slim profile
- Polycarbonate controller
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit (CA versions)
- Fitted with 3000K and 6500K LEDs for colour temperature control

### LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K to 6500K
RATED LIFE (HOURS)	59K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9

**LL/CW 119.9**

For LED characteristics explanation see [www.thorlux.com/led-characteristics](http://www.thorlux.com/led-characteristics)

### RANGE

#### COLOURACTIVE LUMINAIRE - with integral wireless SmartScan Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	LENGTH (mm)
1500	30W	<b>KB 18813CA</b>	4.1	1560
	37W	<b>KB 18814CA</b>	4.1	

#### COLOURCONTROL LUMINAIRE - for use with SmartScan Stand-alone Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	LENGTH (mm)
1500	30W	<b>KB 18816CC</b>	4.1	1510
	37W	<b>KB 18817CC</b>	4.1	

EMERGENCY VERSION - prefix catalogue number with:

**EKB** - Emergency / **TKB** - AutoTest / **WKB** - SmartScan (CA versions only) e.g. **WKB18813CA** etc.

Add 0.3kg to weights listed



### DIMENSIONS

