

FLUTE





LEDs covered by satin tube to reduce glare and diffuse light



Aluminium reflector version

Polycarbonate refractor version

INTEGRAL LED PENDANTS



SPECIFICATION

- Refractor in polycarbonate and reflector in anodised aluminium
- Gloss silver finish extruded aluminium body
- Satin tube over LEDs reduces glare and diffuses light
- Fitted with 2m black cable
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	77K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9

LL/CW **105.4**


For LED characteristics explanation see www.thorlux.com/led-guide

RANGE

LED	CAT. No.	HEIGHT (mm)	DIAMETER (mm)	APPROX. kg
Polycarbonate Refractor				
24W	SH 15156L	365	312	2.0
36W	SH 15157L	365	312	2.0
Aluminium Reflector				
24W	SH 15158L	365	312	2.0
36W	SH 15159L	365	312	2.0


CIRCUIT TYPE - L - non-dimming (LED)

PHOTOMETRIC GUIDE



REFRACTOR

Luminaire Lumen Output:
24W = 2845lm
36W = 4095lm



REFLECTOR

Luminaire Lumen Output:
24W = 1835lm
36W = 2640lm