



## RECESSED LUMINAIRES FOR CORRIDOR APPLICATIONS



### SPECIFICATION

- Steel body, welded and finished steel frame, finished full polyester non-yellowing satin white (RAL 9016)
- Ultra low glare V-blade louvre or general low glare faceted cross-blade louvre set behind a clear polycarbonate cover
- Satin polycarbonate cover version
- Snap fix screw-less frame
- Supplied with side arm suspension kit
- Fits 24mm exposed T-bar ceilings (other ceiling type options available to special order)
- Fitted with 4000K LEDs

### LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	50K - L70/B10
PROTECTION	-
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9

LL/CW **79.1**

For LED characteristics explanation see [www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

### RANGE

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	CIRCUIT
<b>V-blade louvre versions</b>				
1200 x 150	46W	<b>GP 16249</b>	6.7	L/A
<b>Faceted cross-blade louvre versions</b>				
1200 x 150	46W	<b>GP 16251</b>	6.7	L/A
<b>Satin polycarbonate versions</b>				
1200 x 150	46W	<b>GP 16253</b>	5.7	L/A

**CIRCUIT TYPE** - suffix catalogue number with:

**L** - non-dimming (LED) / **A** - dimming (DALI) e.g. **GP 16249L** etc.

**EMERGENCY VERSION** - prefix catalogue number with:

**EGP** - Emergency / **TGP** - AutoTest / **DGP** - Scanlight AT e.g. **EGP 16249L** etc.  
Add 0.3kg to weights listed.

### DIMENSIONS

