





RECESSED SQUARE WALL WASH LUMINAIRES



SPECIFICATION

- Steel bezel finished full polyester, satin white
- Black and silver finishes available to special order*
- Asymmetric distribution providing uniform illumination of vertical surfaces
- Supplied with remote gear unit fitted with 2m lead
- Luminaires can be supplied pre-wired with a purpose made 1m connection lead for plugging directly into the Smart Hub
- 3000K or 4000K versions

* Minimum order quantity applies

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000/4000K
RATED LIFE (HOURS)	50K - L70/B10
PROTECTION	-
DRIVER EFFICIENCY	>80%
REPLACEABLE	-
POWER FACTOR	>0.9

LL/CW 100.8

For LED characteristics explanation see www.thorlux.com/led-guide

RANGE

LED	CAT. No.	APPROX. kg	CIRCUIT
17W - 3000K	QR 18050	1.9	L/A
26W - 3000K	QR 18051	1.9	L/A
41W - 3000K	QR 18052	1.9	L/A
17W - 4000K	QR 18053	1.9	L/A
26W - 4000K	QR 18054	1.9	L/A
41W - 4000K	QR 18055	1.9	L/A


CIRCUIT TYPE - suffix catalogue number with:

L - non-dimming (LED) / **A** - dimming (DALI) e.g. **QR 18050L** etc.

HUB VERSIONS - suffix catalogue number with **SHL**

e.g. **QR 18050SHL**

PHOTOMETRIC GUIDE



LED	3000K (lm)	4000K (lm)
17W	1875	2015
26W	2665	2865
41W	3745	4025

DIMENSIONS

