

# EIGHT-65



## LED EMERGENCY BULKHEAD LUMINAIRES



### SPECIFICATION

- Off-white polycarbonate body
- Opal or clear prismatic polycarbonate covers
- May be semi-recessed
- High light output when operating from integral nickel cadmium battery during mains failure
- Three hour, maintained or non-maintained operation
- Optional self-adhesive legend kit
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas
- Fitted with 4000K LEDs

## RANGE

LED	OPAL VERSION	CLEAR VERSION	APPROX. kg	TYPE
Mains				
4W	<b>FB 18536L</b>	<b>FB 18537L ▲</b>	1.7	
Emergency				
4W	<b>EFB 18538L</b>	<b>EFB 18540L ▲</b>	2.0	Maintained
4W	<b>EFB 18539</b>	<b>EFB 18541 ▲</b>	1.8	Non-maintained
AutoTest				
4W	<b>TFB 18538L</b>	<b>TFB 18540L ▲</b>	2.0	Maintained
4W	<b>TFB 18539</b>	<b>TFB 18541 ▲</b>	1.8	Non-maintained

CIRCUIT TYPE - L - non-dimming (LED)

▲ Not suitable for use with Legend Kits. Opal versions recommended

## LED CHARACTERISTICS

CRI	<b>80+</b>
COLOUR TEMPERATURE	<b>4000K</b>
RATED LIFE (HOURS)	<b>50K - L70/B10</b>
PROTECTION	-
DRIVER EFFICIENCY	<b>&gt;60%</b>
REPLACEABLE	<b>YES</b>
POWER FACTOR	<b>&gt;0.60</b>

**LL/CW 97.5**

For LED characteristics explanation see  
[www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

## LEGEND KITS

ISO 7010 self adhesive legend kit (inc. A, B, C and D) - Cat. No. EFB 15258\*




EURO self adhesive legend kit (inc. E, F and G) - Cat. No. EFB 9137\*



\* Order separately from luminaire



## DIMENSIONS



Semi-recessed mounting cut-out  
149 x 389mm maximum