

SMALL LED EMERGENCY BULKHEAD LUMINAIRES



SPECIFICATION

- Off-white polycarbonate body
- Clear linear prismatic or opal polycarbonate covers
- Emergency and AutoTest versions
- Three hour, maintained or non-maintained operation
- Optional self-adhesive legend kit
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	60K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>60%
REPLACEABLE	YES
POWER FACTOR	0.6

LL/CW **105.8**

For LED characteristics explanation see www.thorlux.com/led-guide




RANGE

LED	OPAL VERSION	CLEAR VERSION	APPROX. kg	TYPE
Emergency				
4W	EFB 15466	EFB 15477 ▲	3.3	Maintained
4W	EFB 15467	EFB 15478 ▲	3.0	Non-maintained
AutoTest				
4W	TFB 15466	TFB 15477 ▲	3.3	Maintained
4W	TFB 15467	TFB 15478 ▲	3.0	Non-maintained

▲ Not suitable for use with Legend Kits. Opal versions recommended

DIMENSIONS



LEGEND KITS



ISO 7010 self adhesive legend kit (inc. A, B, C and D) - Cat. No. EFB 15258*



EURO self adhesive legend kit (inc. E, F and G) - Cat. No. EFB 9137*



* Order separately from luminaire