


# SEVEN




## DIMENSIONS


Ceiling Mounting



Wall Mounting



Cantilever Mounting





## ARCHITECTURAL SURFACE MOUNTED LED EXIT SIGNS

IP20 CE LED

### SPECIFICATION

- Polycarbonate body finished matt silver
- Acrylic legend panel
- Simple to install, full status reporting SmartScan wireless communication versions
- Uses 8 low power consumption long life LEDs (4W total)
- Very easy battery compartment access
- Ceiling mounted or optional kit for wall and cantilever mounting
- Three hour, maintained emergency operation
- Choice of legends

### SmartScan Configurations




Find out more at [www.thorlux.com/smartscan](http://www.thorlux.com/smartscan)

## RANGE


ISO 7010 LEGEND	CAT. No	EURO LEGEND	CAT. No	APPROX. kg	TYPE
<b>AutoTest</b>					
A	TSV 15245	F	TSV 13626	1.0	Maintained
B	TSV 15246	G	TSV 13627	1.0	Maintained
C	TSV 15247	H	TSV 13628	1.0	Maintained
D	TSV 15248	J	TSV 13629	1.0	Maintained
E	TSV 15249			1.0	Maintained
<b>SmartScan</b>					
A	WSV 15245	F	WSV 13626	1.0	Maintained
B	WSV 15246	G	WSV 13627	1.0	Maintained
C	WSV 15247	H	WSV 13628	1.0	Maintained
D	WSV 15248	J	WSV 13629	1.0	Maintained
E	WSV 15249			1.0	Maintained

## LEGEND OPTIONS

### ISO 7010 Single Sided



### EURO Single Sided



### ISO 7010 Double Sided



### EURO Double Sided



## OPTIONAL MOUNTING KIT

DESCRIPTION	APPROX. kg	CAT. No.
Wall or cantilever mounting kit	0.2	SV 13630