



KANBY LED CONTROLLER



Smart version

Narrow body

Wide body

LED CONTROLLER LUMINAIRES



SPECIFICATION

- Steel body, gear cover and end caps finished full polyester, non-yellowing white
- Ultra slim profile
- Polycarbonate controller
- Smart versions with intelligent lighting control
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	90K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9

LL/CW 142.2

For LED characteristics explanation see www.thorlux.com/led-guide

SmartScan Configurations



Find out more at www.thorlux.com/smartsan

RANGE

	NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	LENGTH (mm)	FIXINGS	CIRCUIT
SMART	1500	21W	KB 17606 ■	3.3	1560	Suitable for BESA fixing on 600 to 610mm centres	D/SS
		28W	KB 16107 ■	3.3			D/SS
		37W	KB 16108 ■	3.3			D/SS
		49W	KB 16103 ▲	4.1			D/SS
		63W	KB 16104 ▲	4.1			D/SS
STANDARD	1500	21W	KB 17607 ■	3.2	1510	As above	L/A
		28W	KB 16105 ■	3.2			L/A
		37W	KB 16106 ■	3.2			L/A
		49W	KB 16101 ▲	4.0			L/A
		63W	KB 16102 ▲	4.0			L/A

CIRCUIT TYPE - suffix catalogue number with:

SMART D - Smart / SS - SmartScan

STANDARD L - non-dimming (LED) / A - dimming (DALI) e.g. KB 17606SS etc.

EMERGENCY VERSION - prefix catalogue number with:


EKB - Emergency } (Not available when selecting the 'SS' suffix)
TKB - AutoTest

WKB - SmartScan (Only available when selecting the 'SS' suffix)
e.g. WKB 17606SS etc.

Add 0.3kg to weights listed


■ Narrow body / ▲ Wide body

PHOTOMETRIC GUIDE



WIDE BODY

Luminaire Lumen Output:
49W = 7670lm
63W = 9465lm



NARROW BODY

Luminaire Lumen Output:
21W = 3555lm
28W = 4590lm
37W = 5860lm

DIMENSIONS

