




Hi-Style LED

HIGH PERFORMANCE RECESSED COLOUR TEMPERATURE CHANGING LED LUMINAIRES



SPECIFICATION

- Steel body finished full polyester non-yellowing satin white (RAL 9016)
- Carefully controlled optics for LG7:2015 (<3000 cd/m² @ 65°) compliance or opal diffuser version
- Fire retardant polycarbonate diffusers for TP(a) compliance
- Excellent wall illumination at high angles
- Balanced direct/indirect luminance control above 65°
- Suitable for most ceiling types with optional side arm suspensions
- Extruded side diffusers give vibrant yet low glare aesthetics
- Designed to exclude dust, dirt and flies
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit (CA versions)
- Fitted with 3000K and 6500K LEDs for colour temperature control

SmartScan Configurations



Find out more at www.thorlux.com/smartscan

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K to 6500K
RATED LIFE (HOURS)	67K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9
LL/CW	124.2

For LED characteristics explanation see www.thorlux.com/led-guide

RANGE

COLOURACTIVE LUMINAIRE - with integral wireless SmartScan Sensor

NOMINAL SIZE (mm)	LED	LG7:2015	OPAL	APPROX. kg
600 X 600	16W	HI 18526CA	HI 18523CA	4.9
	24W	HI 18527CA	HI 18524CA	4.9
	34W	HI 19132CA	HI 19130CA	4.9

COLOURCONTROL LUMINAIRE - for use with SmartScan Stand-alone Sensor

NOMINAL SIZE (mm)	LED	LG7:2015	OPAL	APPROX. kg
600 X 600	16W	HI 18532CC	HI 18529CC	4.8
	24W	HI 18533CC	HI 18530CC	4.8
	34W	HI 19133CC	HI 19131CC	4.8

EMERGENCY VERSION - prefix catalogue number with:


EHI - Emergency
THI - AutoTest

WHI - SmartScan (Only available when selecting the 'CA' suffix)
e.g. WHI 18526CA etc.

Add 0.3kg to weights listed



DIMENSIONS



ACCESSORIES

DESCRIPTION	CAT. No.
Optional side arm suspension kit (4 arms per kit - not required for lay-in mounting)	HI 12349

WEB LINK >

"PLUG AND PLAY"
LIGHTING CABLE
MANAGEMENT

