

NET 16


Serie di apparecchi tubulari dalle linee essenziali e pulite strutturato in alluminio e policarbonato. Offre molte possibilità di realizzazione. Driver remoto escluso.

Minimal tubular lighting fitting for various installations. Structure in aluminium and polycarbonate. Remote driver excluded.




○ 05- anodizzato / anodised

120 LED / M




CODICE / CODE	L.MM	w	LM	DIFFUSORE / DIFFUSER
NES.3341.1 6 Y.05	1050	9,6W/24V LED	780/720	acidato/clear
NES.3341.2 6 Y.05	2050	19,2W/24V LED	1560/1440	acidato/clear
NES.3341.3 6 Y.05	3050	28,8W/24V LED	2340/2160	acidato/clear

60 LED / M




CODICE / CODE	L.MM	w	LM	DIFFUSORE / DIFFUSER
NES.3342.1 6 Y.05	1050	14,4W/24V LED	1060/990	acidato/clear
NES.3342.2 6 Y.05	2050	28,8W/24V LED	2120/1980	acidato/clear
NES.3342.3 6 Y.05	3050	43,2W/24V LED	3180/2970	acidato/clear

120 LED / M



CODICE / CODE	L.MM	w	LM	DIFFUSORE / DIFFUSER
NES.3351.1 6 Y.05	1050	9,6W/24V LED	780/720	opale/opal
NES.3351.2 6 Y.05	2050	19,2W/24V LED	1560/1440	opale/opal
NES.3351.3 6 Y.05	3050	28,8W/24V LED	2340/2160	opale/opal

60 LED / M



CODICE / CODE	L.MM	w	LM	DIFFUSORE / DIFFUSER
NES.3352.1 6 Y.05	1050	14,4W/24V LED	1060/990	opale/opal
NES.3352.2 6 Y.05	2050	28,8W/24V LED	2120/1980	opale/opal
NES.3352.3 6 Y.05	3050	43,2W/24V LED	3180/2970	opale/opal

ACCESSORI / ACCESSORIES



CODICE / CODE	DESCRIZIONE / DESCRIPTION
AAA.TRSL08	Driver LED IP20 30W.
AAA.TRSL09	Driver LED IP20 75W.
AAA.TRSL10	Driver LED IP20 150W.
AAA.TRSL13	Driver LED IP67 70W.
AAA.TRSL15	Driver LED IP65 10W.



NES.SO Sospensioni (coppia). Suspension kit (pair).