


## Luminaire

Code SAL  
Name Salina 10W 15D  
Measurement  
Code sal102019  
Name Salina 10W 15D

Luminaire Flux	529.20 lm	Luminaire Power	10.00 W	Efficacy	52.92 lm/W	Efficiency	103.76%
Lamps Flux	510.00 lm	Maximum value	5114.64 cd/klm	Position	C=90.00 G=0.00	CG	Asymmetrical
Round Luminaire		Diam.	71 mm	Height	20 mm		
Round Luminous Area		Diam.	45 mm	Height	0 mm		
Horizontal Luminous Area		0.001590 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000385 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		27-01-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		510.00 lm	
Operator				Source Voltage [V]		230.00 V	
Temperature		25.00 °C		Source current [A]			
Humidity		60.00 %		Photocell			
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	Led	Name	510.00	10.00	1
	Led	Led			
C.I.E.	99 100 100 99 104	D DIN 5040	A61		
F UTE	--	B NBN	BZ 1		



ULOR 1.26 %  
DLOR102.51 %  
RN 1.21 %

