


# GLODOME




## PHOTOMETRIC GUIDE



Luminaire Lumen Output:  
 8W = 1290lm  
 16W = 2385lm  
 20W = 2990lm  
 26W = 3945lm

## DIMENSIONS





## SURFACE MOUNTED LED LUMINAIRES



### SPECIFICATION

- Spun aluminium body finished full polyester, non-yellowing white
- Textured opal polycarbonate cover
- Smart version with intelligent lighting control
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit
- SmartScan Radar versions with sensor discretely hidden behind the cover
- Fitted with 4000K LEDs

### LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	100K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	88%
REPLACEABLE	YES
POWER FACTOR	>0.95

LL/CW **136.0**

For LED characteristics explanation see [www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

### SmartScan Configurations



Find out more at [www.thorlux.com/smartsan](http://www.thorlux.com/smartsan)

### RANGE

	LED	CAT. No.	CIRCUIT	APPROX. kg
CONTROLLED	Small version 20W	<b>GLO 17426</b>	D/SS/R	1.2
	Small version 8W 16W 20W	<b>GLO 17405</b> <b>GLO 16483</b> <b>GLO 16484</b>	L/A L/A L/A	1.1 1.1 1.1
STANDARD	Large version 26W	<b>GLO 15856</b>	L/A	2.1

CIRCUIT TYPE - suffix catalogue number with:

**CONTROLLED** D - Smart / SS - SmartScan / R - SmartScan Radar  
**STANDARD** L - non-dimming (LED) / A - dimming (DALI)  
 e.g. **GLO 17426SS** etc.

EMERGENCY VERSION - prefix catalogue number with:

**EGL** - Emergency  
**TGL** - AutoTest (Not available when selecting the 'SS' or 'R' suffix)  
**WGL** - SmartScan (16W and 20W only)  
 e.g. **WGL 17426SS** etc.  
 Add 0.3kg to weights listed

### ACCESSORIES

DESCRIPTION	CAT. No.
IP54 sealing gasket - small version	<b>GLO 16485</b>
IP54 sealing gasket - large version	<b>GLO 16539</b>
Conduit adaptor - small version	<b>GLO 17433</b>



Presence Detection Guide - [www.thorlux.com/files/presence-detection.pdf](http://www.thorlux.com/files/presence-detection.pdf)