

LUX OUTDOOR MB WW

Installation :

Project number :

Customer :

Processed by :

Date : 17.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : LUX OUTDOOR MB WW
Installation :
Project number :
Date : 17.03.2020

1 Luminaire data

1.1 NEMO Studio, LUX OUTDOOR MB WW (BLUX0201417WCS)

1.1.1 Data sheet

Manufacturer: NEMO Studio

BLUX0201417WCS

LUX OUTDOOR MB WW


Luminaire data

Luminaire efficacy : 56.7 lm/W
Classification : A80 ↓99.9% ↑0.1%
CIE Flux Codes : 98 99 100 100 105
UGR 4H 8H : <10.0 / <10.0
Power : 1.2 W

Equipped with


Quantity : 1
Designation : Source
Colour : 3040 K
Luminous flux : 68 lm
Colour reproduction : 90

Dimensions : Ø44 mm x 56 mm



1.1 NEMO Studio, LUX OUTDOOR MB WW (BLUX0201417WCS)

1.1.2 LDC




Manufacturer : NEMO Studio
 Order number : BLUX0201417WCS
 Luminaire name : LUX OUTDOOR MB WW
 Equipment : 1 x Source 1.2 W / 68 lm
 Dimensions : D 44 mm x H 56 mm
 File name : BLUX0201417WCS.LDT

Luminaire efficacy : 56.7 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 23.8° C0-C180

1.1 NEMO Studio, LUX OUTDOOR MB WW (BLUX0201417WCS)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer : NEMO Studio
 Order number : BLUX0201417WCS
 Luminaire name : LUX OUTDOOR MB WW
 Equipment : 1 x Source 1.2 W / 68 lm
 Dimensions : D 44 mm x H 56 mm
 File name : BLUX0201417WCS.LDT

Luminaire efficacy : 56.7 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 23.8° C0-C180