



## WALL MOUNTED LED UP AND DOWNLIGHTERS



### SPECIFICATION

- White injection moulded polycarbonate body (RAL 9016)
- Silver option (RAL 9006)
- High efficiency satin polycarbonate covers
- Can be mounted horizontally or vertically
- Up and downlighter or uplighter only version
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit
- Fitted with 4000K LEDs

### LED CHARACTERISTICS

|                    |                |
|--------------------|----------------|
| CRI                | 80+            |
| COLOUR TEMPERATURE | 4000K          |
| RATED LIFE (HOURS) | 100K - L80/B10 |
| PROTECTION         | LUX GUARD      |
| DRIVER EFFICIENCY  | >80%           |
| REPLACEABLE        | YES            |
| POWER FACTOR       | >0.95          |
| LL/CW              | 134.6          |


For LED characteristics explanation see [www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

### SmartScan Configurations



Find out more at [www.thorlux.com/smartsan](http://www.thorlux.com/smartsan)

### PHOTOMETRIC GUIDE



Luminaire Lumen Output  
10W = 1560lm  
20W = 3095lm

### RANGE

|          | LED                    | CAT. No. | APPROX. kg | CIRCUIT |
|----------|------------------------|----------|------------|---------|
| SMART    | Up and downlighter 20W | CA 19183 | 1.8        | D/SS    |
|          | Uplighter 10W          | CA 19182 | 1.7        | D/SS    |
| STANDARD | Up and downlighter 20W | CA 15854 | 1.7        | L/A     |
|          | Uplighter 10W +        | CA 15853 | 1.6        | L/A     |

CIRCUIT TYPE - suffix catalogue number with:

|          |  |
|----------|--|
| SMART    | D - Smart / SS - SmartScan   |
| STANDARD | L - non-dimming (LED) / A - dimming (DALI)<br>e.g. CA 19183SS etc. |

EMERGENCY VERSION - prefix catalogue number with:

ECA - Emergency  
TCA - AutoTest

WCA - SmartScan (Only available when selecting the 'SS' suffix)  
e.g. WCA 19183SS etc.

Add 0.3kg to weights listed

FINISH OPTION - suffix catalogue number with:

SV3 - Silver e.g. CA 15854LSV3 etc.

+ Can also be used as a downlighter



### DIMENSIONS

