

KIOPS MB 3000K

Installation :

Project number :

Customer :

Processed by :

Date : 17.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : KIROPS MB 3000K
Installation :
Project number :
Date : 17.03.2020

1 Luminaire data

1.1 NEMO STUDIO, KIROPS MB 3000K 2000lm (MKIR0902502WGP)

1.1.1 Data sheet

Manufacturer: NEMO STUDIO

MKIR0902502WGP

KIROPS MB 3000K 2000lm


Luminaire data

Luminaire efficacy : 85.1 lm/W
Classification : A80 ↓100.0% ↑0.0%
CIE Flux Codes : 95 98 100 100 106
UGR 4H 8H : 15.1 / 15.1
Power : 19 W

Equipped with


Quantity : 1
Designation : Source
Colour : 3000 K
Luminous flux : 1617 lm
Colour reproduction : 80

Dimensions : Ø140 mm x 221 mm



1.1 NEMO STUDIO, KIOPS MB 3000K 2000lm (MKIR0902502WGP)

1.1.2 LDC




Manufacturer : NEMO STUDIO
 Order number : MKIR0902502WGP
 Luminaire name : KIOPS MB 3000K 2000lm
 Equipment : 1 x Source 19 W / 1617 lm
 Dimensions : D 140 mm x H 221 mm
 File name : MKIR0902502WGP.LDT

Luminaire efficacy : 85.1 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 19.6° C0-C180

1.1 NEMO STUDIO, KIROPS MB 3000K 2000lm (MKIR0902502WGP)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer : NEMO STUDIO
 Order number : MKIR0902502WGP
 Luminaire name : KIROPS MB 3000K 2000lm
 Equipment : 1 x Source 19 W / 1617 lm
 Dimensions : D 140 mm x H 221 mm
 File name : MKIR0902502WGP.LDT

Luminaire efficacy : 89.99 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 19.6° C0-C180