



LIGHTING CABLE MANAGEMENT - SMARTSCAN

3-POLE INTERCONNECTING LEADS FOR USE WITH SMARTSCAN RECESSED LUMINAIRES



SPECIFICATION

- Thorlux UK designed and manufactured
- LSOH - low smoke zero halogen cables
- Leads can be plugged together to extend wiring
- Future flexibility - plug and play
- Twin latch design - strong strain relief
- Constructed from flame-retardant nylon
- Compliance with new standard BS EN 61535:2013



Connection lead
3-pole connectors with 3-core cable 1.5mm²
3m - LCM 18270
4m - LCM 18271
6m - LCM 18272



Starter lead
3-pole mains plug with 3-core input cable stripped at one end 1.5mm²
3m - LCM 18273



Connector
3-pole
Live end (for connection to luminaire) - LCM 18276
Dead end (for connection from luminaire) - LCM 18277



Connection lead
3-pole plug with 3-core cable stripped at one end 0.75mm² (for non factory fitted luminaires)
3m - LCM 14822



Hub extension lead
3-pole connectors with 3-core cable 1.5mm²
3m - LCM 14823



Circuit splitter
LCM 14928



Permanent Live (L)
⊕
Neutral

NOTE:
If modular wiring is not required please suffix luminaire catalogue number with **NT** e.g. **XL 18306SSNT**