


## Luminaire

Code CAP  
Name Capri 28W 15D  
**Measurem.**  
Code cap042020  
Name Capri 28W 15D

Luminaire Flux	1493.82 lm	Luminaire Power	28.00 W	Efficacy	53.35 lm/W	Efficiency	106.42%
Lamps Flux	1403.70 lm	Maximum value	8687.38 cd/klm	Position	C=90.00 G=0.00	CG	Asymmetrical
Round Luminaire		Diam.	73 mm	Height	170 mm		
Round Luminous Area		Diam.	45 mm	Height	0 mm		
Horizontal Luminous Area		0.001590 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000385 m2	
Coordinate system	CG			Symmetry Type		Asymmetrical	
Date	27-01-2000			Maximum Gamma Angle		180	
Measurement Distance	0.00			Measurement Flux		1403.70 lm	
Operator				Source Voltage [V]		230.00 V	
Temperature	25.00 °C			Source current [A]			
Humidity	60.00 %			Photocell			
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	Led	Name Led	1403.70	28.00	1
C.I.E.	98 100 100 99 106	D DIN 5040	A61		
F UTE	--	B NBN	BZ 1		



ULOR 1.27 %  
DLOR105.15 %  
RN 1.19 %

