


## Luminaire

Code CAP  
Name Capri 28W 55D  
Measurem.  
Code cap042020  
Name Capri 28W 55D

Luminaire Flux	1676.92 lm	Luminaire Power	28.00 W	Efficacy	59.89 lm/W	Efficiency	100.81%
Lamps Flux	1663.40 lm	Maximum value	1268.85 cd/klm	Position	C=45.00 G=0.00	CG	Asymmetrical
Round Luminaire	Diam.	73 mm	Height	170 mm			
Round Luminous Area	Diam.	45 mm	Height	0 mm			
Horizontal Luminous Area	0.001590 m2		Emitting area on Plane 180°		0.000000 m2		
Emitting area on Plane 0°	0.000000 m2		Emitting area on Plane 270°		0.000000 m2		
Emitting area on Plane 90°	0.000000 m2		Glare area at 76°		0.000385 m2		
Coordinate system	CG	Symmetry Type			Asymmetrical		
Date	27-01-2000	Maximum Gamma Angle			180		
Measurement Distance	0.00	Measurement Flux			1663.40 lm		
Operator				Source Voltage [V]	230.00 V		
Temperature	25.00 °C	Source current [A]					
Humidity	60.00 %	Photocell					
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	Led	Name Led	1663.40	28.00	1
C.I.E.	97 100 100 99 101	D DIN 5040	A61		
F UTE	1.00 A + 0.01 T	B NBN	BZ 1		



ULOR 1.26 %  
DLOR 99.55 %  
RN 1.25 %

