

## SHARP\_ZOOM 927 - wide

Installation :

Project number :

Customer :

Processed by :

Date : 20.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : SHARP\_ZOOM 927 - wide  
Installation :  
Project number :  
Date : 20.03.2020

## 1 Luminaire data

### 1.1 NEMO Studio, SHARP\_ZOOM 927 - wide (MPFB\_\_01929D\_\_ - wide)

#### 1.1.1 Data sheet

---

**Manufacturer: NEMO Studio**

**MPFB\_\_01929D\_\_ - wide**

**SHARP\_ZOOM 927 - wide**


#### Luminaire data

Luminaire efficacy : 61.84 lm/W  
Classification : A80 ↓100.0% ↑0.0%  
CIE Flux Codes : 97 99 100 100 107  
UGR 4H 8H : 14.3 / 14.3  
Power : 25 W

#### Equipped with


Quantity : 1  
Designation : Source  
Colour : 2750 K  
Luminous flux : 1546 lm  
Colour reproduction : 94

Dimensions : Ø90 mm x 292 mm



## 1.1 NEMO Studio, SHARP\_ZOOM 927 - wide (MPFB\_\_01929D\_\_ - wide)

### 1.1.2 LDC




Manufacturer : NEMO Studio  
 Order number : MPFB\_\_01929D\_\_ - wide  
 Luminaire name : SHARP\_ZOOM 927 - wide  
 Equipment : 1 x Source 25 W / 1546 lm  
 Dimensions : D 90 mm x H 292 mm  
 File name : MPFB\_\_01929D\_\_ wide.LDT

Luminaire efficacy : 61.84 lm/W (A80)  
 Light distribution : rotationally symmetric  
 Beam Angle : 55.6° C0-C180

## 1.1 NEMO Studio, SHARP\_ZOOM 927 - wide (MPFB\_\_01929D\_\_ - wide)

### 1.1.3 Cone diagram



Note: The illuminance is calculated with  $I(\gamma=0)!$

Manufacturer : NEMO Studio  
 Order number : MPFB\_\_01929D\_\_ - wide  
 Luminaire name : SHARP\_ZOOM 927 - wide  
 Equipment : 1 x Source 25 W / 1546 lm  
 Dimensions : D 90 mm x H 292 mm  
 File name : MPFB\_\_01929D\_\_ wide.LDT

Luminaire efficacy : 61.84 lm/W (A80)  
 Light distribution : rotationally symmetric  
 Beam Angle : 55.6° C0-C180