

Lux 33 gen2 CW WB

Installation :

Project number :

Customer :

Processed by :

Date : 23.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : Lux 33 gen2 CW WB
Installation :
Project number :
Date : 23.03.2020

1 Luminaire data

1.1 NEMO Studio, Lux 33 gen2 CW WB (BLUX09097170AN)

1.1.1 Data sheet

Manufacturer: NEMO Studio

BLUX09097170AN Lux 33 gen2 CW WB


Luminaire data

Luminaire efficacy : 82.86 lm/W
Classification : A70 ↓100.0% ↑0.0%
CIE Flux Codes : 93 98 100 100 100
UGR 4H 8H : 16.2 / 16.2
Power : 14 W

Equipped with


Quantity : 1
Designation : Source
Colour : 5000 K
Luminous flux : 1160 lm
Colour reproduction : 80

Dimensions : Ø100 mm x 109 mm



1.1 NEMO Studio, Lux 33 gen2 CW WB (BLUX09097170AN)

1.1.2 LDC




Manufacturer : NEMO Studio
 Order number : BLUX09097170AN
 Luminaire name : Lux 33 gen2 CW WB
 Equipment : 1 x Source 14 W / 1160 lm
 Dimensions : D 100 mm x H 109 mm
 File name : BLUX09097170AN.LDT

Luminaire efficacy : 82.86 lm/W (A70)
 Light distribution : rotationally symmetric
 Beam Angle : 32.5° C0-C180

1.1 NEMO Studio, Lux 33 gen2 CW WB (BLUX09097170AN)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer : NEMO Studio
 Order number : BLUX09097170AN
 Luminaire name : Lux 33 gen2 CW WB
 Equipment : 1 x Source 14 W / 1160 lm
 Dimensions : D 100 mm x H 109 mm
 File name : BLUX09097170AN.LDT

Luminaire efficacy : 82.86 lm/W (A70)
 Light distribution : rotationally symmetric
 Beam Angle : 32.5° C0-C180