

## LUX 33 gen.2 CW MB

Installation :

Project number :

Customer :

Processed by :

Date : 23.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : LUX 33 gen.2 CW MB  
Installation :  
Project number :  
Date : 23.03.2020

## 1 Luminaire data

### 1.1 NEMO Studio, LUX 33 gen.2 CW MB (BLUX09094170AN)

#### 1.1.1 Data sheet

---

**Manufacturer: NEMO Studio**

**BLUX09094170AN      LUX 33 gen.2 CW MB**


#### Luminaire data

Luminaire efficacy : 90 lm/W  
Classification : A80 ↓100.0% ↑0.0%  
CIE Flux Codes : 96 99 100 100 114  
UGR 4H 8H : 13.8 / 13.8  
Power : 14 W

#### Equipped with


Quantity : 1  
Designation : Source  
Colour : 5000 K  
Luminous flux : 1260 lm  
Colour reproduction : 90

Dimensions : Ø100 mm x 109 mm



## 1.1 NEMO Studio, LUX 33 gen.2 CW MB (BLUX09094170AN)

### 1.1.2 LDC




Manufacturer : NEMO Studio  
 Order number : BLUX09094170AN  
 Luminaire name : LUX 33 gen.2 CW MB  
 Equipment : 1 x Source 14 W / 1260 lm  
 Dimensions : D 100 mm x H 109 mm  
 File name : BLUX09094170AN.LDT

Luminaire efficacy : 90 lm/W (A80)  
 Light distribution : rotationally symmetric  
 Beam Angle : 24.9° C0-C180

## 1.1 NEMO Studio, LUX 33 gen.2 CW MB (BLUX09094170AN)

### 1.1.3 Cone diagram



Note: The illuminance is calculated with  $I(\gamma=0)$ !

Manufacturer : NEMO Studio  
 Order number : BLUX09094170AN  
 Luminaire name : LUX 33 gen.2 CW MB  
 Equipment : 1 x Source 14 W / 1260 lm  
 Dimensions : D 100 mm x H 109 mm  
 File name : BLUX09094170AN.LDT

Luminaire efficacy : 90 lm/W (A80)  
 Light distribution : rotationally symmetric  
 Beam Angle : 24.9° C0-C180