

LUX 33 gen2 RGB WB

Installation :

Project number :

Customer :

Processed by :

Date : 24.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : LUX 33 gen2 RGB WB
Installation :
Project number :
Date : 24.03.2020

1 Luminaire data

1.1 NEMO Studio, LUX 33 RGB gen.2 WB (BLUX09067306AN)

1.1.1 Data sheet

Manufacturer: NEMO Studio

BLUX09067306AN

LUX 33 RGB gen.2 WB


Luminaire data

Luminaire efficacy : 32.64 lm/W
Classification : A80 ↓100.0% ↑0.0%
CIE Flux Codes : 94 98 100 100 98
UGR 4H 8H : 11.9 / 11.9
Power : 11 W

Equipped with


Quantity : 1
Designation : Source
Colour : RGB
Luminous flux : 359 lm
Colour reproduction : 20

Dimensions : Ø100 mm x 109 mm



1.1 NEMO Studio, LUX 33 RGB gen.2 WB (BLUX09067306AN)

1.1.2 LDC




Manufacturer : NEMO Studio
 Order number : BLUX09067306AN
 Luminaire name : LUX 33 RGB gen.2 WB
 Equipment : 1 x Source 11 W / 359 lm
 Dimensions : D 100 mm x H 109 mm
 File name : BLUX09067306AN.LDT

Luminaire efficacy : 32.64 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 30.9° C0-C180

1.1 NEMO Studio, LUX 33 RGB gen.2 WB (BLUX09067306AN)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)$!

Manufacturer : NEMO Studio
 Order number : BLUX09067306AN
 Luminaire name : LUX 33 RGB gen.2 WB
 Equipment : 1 x Source 11 W / 359 lm
 Dimensions : D 100 mm x H 109 mm
 File name : BLUX09067306AN.LDT

Luminaire efficacy : 32.64 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 30.9° C0-C180