

MINIFLUX Opal 1m NW

Installation :

Project number :

Customer :

Processed by :

Date : 19.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : MINIFLUX Opal 1m NW
Installation :
Project number :
Date : 19.03.2020

1 Luminaire data

1.1 NEMO Studio, MINIFLUX OPAL NW 1m (BBOK0910G26NPO)

1.1.1 Data sheet

Manufacturer: NEMO Studio

BBOK0910G26NPO

MINIFLUX OPAL NW 1m


Luminaire data

Luminaire efficacy : 63.2 lm/W
Classification : A30 ↓98.4% ↑1.6%
CIE Flux Codes : 37 66 87 98 109
UGR 4H 8H : 31.2 / 29.1
Power : 15 W

Equipped with


Quantity : 1
Designation : Source
Colour : 4000 K
Luminous flux : 948 lm
Colour reproduction : 94

Dimensions : 1030 mm x 20 mm x 20 mm



1.1 NEMO Studio, MINIFLUX OPAL NW 1m (BBOK0910G26NPO)

1.1.2 LDC




Manufacturer : NEMO Studio
Order number : BBOK0910G26NPO
Luminaire name : MINIFLUX OPAL NW 1m
Equipment : 1 x Source 15 W / 948 lm
Dimensions : L 1030 mm x W 20 mm x H 20 mm
File name : BBOK0910G26NPO.LDT

Luminaire efficacy : 63.2 lm/W (A30)
Light distribution : sym. to C0-C180 / C90-C270
Beam Angle : 145.8° C0-C180
130.2° C90-C270

1.1 NEMO Studio, MINIFLUX OPAL NW 1m (BBOK0910G26NPO)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)$!

Manufacturer	: NEMO Studio	Luminaire efficacy	: 63.2 lm/W (A30)
Order number	: BBOK0910G26NPO	Light distribution	: sym. to C0-C180 / C90-C270
Luminaire name	: MINIFLUX OPAL NW 1m	Beam Angle	: 145.8° C0-C180
Equipment	: 1 x Source 15 W / 948 lm		: 130.2° C90-C270
Dimensions	: L 1030 mm x W 20 mm x H 20 mm		
File name	: BBOK0910G26NPO.LDT		