

## MINIFLUX Opal 1m WW

Installation :

Project number :

Customer :

Processed by :

Date : 19.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : MINIFLUX Opal 1m WW  
Installation :  
Project number :  
Date : 19.03.2020

## 1 Luminaire data

### 1.1 NEMO Studio, MINIFLUX OPAL WW 1m (BBOK0910G26WPO)

#### 1.1.1 Data sheet

---

**Manufacturer: NEMO Studio**

**BBOK0910G26WPO**

**MINIFLUX OPAL WW 1m**


#### Luminaire data

Luminaire efficacy : 60.4 lm/W  
Classification : A30 ↓98.4% ↑1.6%  
CIE Flux Codes : 37 66 87 98 110  
UGR 4H 8H : 31.4 / 28.6  
Power : 15 W

#### Equipped with


Quantity : 1  
Designation : Source  
Colour : 3000 K  
Luminous flux : 905 lm  
Colour reproduction : 97

Dimensions : 1030 mm x 20 mm x 20 mm



## 1.1 NEMO Studio, MINIFLUX OPAL WW 1m (BBOK0910G26WPO)

### 1.1.2 LDC




Manufacturer : NEMO Studio  
 Order number : BBOK0910G26WPO  
 Luminaire name : MINIFLUX OPAL WW 1m  
 Equipment : 1 x Source 15 W / 905 lm  
 Dimensions : L 1030 mm x W 20 mm x H 20 mm  
 File name : BBOK0910G26WPO.LDT

Luminaire efficacy : 60.4 lm/W (A30)  
 Light distribution : sym. to C0-C180 / C90-C270  
 Beam Angle : 151.1° C0-C180  
 126.2° C90-C270

## 1.1 NEMO Studio, MINIFLUX OPAL WW 1m (BBOK0910G26WPO)

### 1.1.3 Cone diagram



Note: The illuminance is calculated with  $I(\gamma=0)!$

|                |                                 |                    |                              |
|----------------|---------------------------------|--------------------|------------------------------|
| Manufacturer   | : NEMO Studio                   | Luminaire efficacy | : 60.4 lm/W (A30)            |
| Order number   | : BBOK0910G26WPO                | Light distribution | : sym. to C0-C180 / C90-C270 |
| Luminaire name | : MINIFLUX OPAL WW 1m           | Beam Angle         | : 151.1° C0-C180             |
| Equipment      | : 1 x Source 15 W / 905 lm      |                    | : 126.2° C90-C270            |
| Dimensions     | : L 1030 mm x W 20 mm x H 20 mm |                    |                              |
| File name      | : BBOK0910G26WPO.LDT            |                    |                              |