

## SLACKLINE REGULAR WW 1m

Installation :

Project number :

Customer :

Processed by :

Date : 19.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : SLACKLINE REGULAR WW 1m  
Installation :  
Project number :  
Date : 19.03.2020

## 1 Luminaire data

### 1.1 NEMO Studio, SLACKLINE REGULAR WW 1m (BSLA\_\_10G26WAA)

#### 1.1.1 Data sheet

---

Manufacturer: NEMO Studio

**BSLA\_\_10G26WAA**      **SLACKLINE REGULAR WW 1m**


#### Luminaire data

Luminaire efficacy : 57.5 lm/W  
Classification : A40 ↓99.9% ↑0.1%  
CIE Flux Codes : 44 77 95 100 110  
UGR 4H 8H : 26.1 / 27.9  
Power : 15 W

#### Equipped with

Quantity : 1  
Designation : Source  
Colour : 3050 K  
Luminous flux : 862 lm  
Colour reproduction : 97


Dimensions : 1000 mm x 21 mm x 13 mm



Object : SLACKLINE REGULAR WW 1m  
Installation :  
Project number :  
Date : 19.03.2020

## 1.1 NEMO Studio, SLACKLINE REGULAR WW 1m (BSLA\_\_10G26WAA)

### 1.1.2 LDC




Manufacturer : NEMO Studio  
Order number : BSLA\_\_10G26WAA  
Luminaire name : SLACKLINE REGULAR WW 1m  
Equipment : 1 x Source 15 W / 862 lm  
Dimensions : L 1000 mm x W 21 mm x H 13 mm  
File name : BSLA\_\_10G26WAA.LDT

Luminaire efficacy : 57.5 lm/W (A40)  
Light distribution : sym. to C0-C180 / C90-C270  
Beam Angle : 110.7° C0-C180  
127.1° C90-C270

## 1.1 NEMO Studio, SLACKLINE REGULAR WW 1m (BSLA\_\_10G26WAA)

### 1.1.3 Cone diagram



Note: The illuminance is calculated with  $I(\gamma=0)!$

Manufacturer	: NEMO Studio	Luminaire efficacy	: 57.5 lm/W (A40)
Order number	: BSLA__10G26WAA	Light distribution	: sym. to C0-C180 / C90-C270
Luminaire name	: SLACKLINE REGULAR WW 1m	Beam Angle	: 110.7° C0-C180
Equipment	: 1 x Source 15 W / 862 lm		: 127.1° C90-C270
Dimensions	: L 1000 mm x W 21 mm x H 13 mm		
File name	: BSLA__10G26WAA.LDT		