



DIMENSIONS



ACCESSORIES

DESCRIPTION	CAT. No.	APPROX. kg
597 x 597mm ceiling reinforcing board (3mm thick plywood with 185mm diameter central cut-out)	GT 11970	0.55

WEB LINK >
"PLUG AND PLAY"
LIGHTING CABLE
MANAGEMENT



LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K to 6500K
RATED LIFE (HOURS)	60K - L80/B10
PROTECTION	LED PROTECT
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9

LL/CW **68.3**

For LED characteristics explanation see www.thorlux.com/led-guide

RANGE

COLOURACTIVE LUMINAIRE - with integral wireless SmartScan Sensor

LED	CAT. No.	APPROX. kg
12W	GT 18822CA	1.5
24W	GT 18823CA	1.5

COLOURCONTROL LUMINAIRE - for use with SmartScan Stand-alone Sensor

LED	CAT. No.	APPROX. kg
12W	GT 18824CC	1.5
24W	GT 18825CC	1.5

EMERGENCY VERSION - prefix catalogue number with:

EGT - Emergency
TGT - AutoTest] (Only available when selecting the 'CC' suffix)

e.g. EGT 18824CC etc.

Add 0.3kg to weights listed

NOTE: Emergency not available with ColourActive

CIRCULAR RECESSED COLOUR
TEMPERATURE CHANGING LED
DOWNLIGHTERS



SPECIFICATION

- High pressure die-cast ring finished full polyester, non-yellowing white
- Aluminium heat sink
- Injection moulded reflector finished white
- Optional reinforcing board with centre cut aperture
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit (CA versions)
- Supplied with remote gear unit fitted with 2m lead
- ColourActive versions fitted with 3-pole TEE connector for LCM wiring
- Fitted with 3000K and 6500K LEDs for colour temperature control

SmartScan Configurations



Find out more at www.thorlux.com/smartsan